

## COMBIFIX®

### Fount concentrate for sheet-fed offset

#### 8022 19

for water with a hydrogen carbonate content  
**up to 250 mg/l**

#### 8022 39

for water with a hydrogen carbonate content  
**above 250 mg/l**

#### Application

COMBIFIX® is intended as a standard product for conventional fount application systems in sheet-fed offset.

#### Special properties

- Formation of a stable film of fount solution.
- Specific adjustment of surface tension.
- Good protection of printing plates.
- Effective corrosion inhibitors offer excellent protection for materials.

Despite the good buffer effect of COMBIFIX®, two varieties are necessary in order to permit adjustment of all types of tap water qualities to the range of between pH 5.0 and 5.3 that is most favourable for printing. In case of doubt as to which product should be used, we are offering the service of a free water analysis.

#### Quantity to be added

The recommended concentration for use is 4%.

#### Special versions

##### COMBIFIX® 8039 09

Fount concentrate for metallic inks.

#### Labelling

German Hazardous Substances Ordinance (GefStoffV): Irritant (Xi)

Safety data sheet available on request.

#### How supplied

10-kg plastic containers  
220-kg plastic drums

---

Contact addresses for advice and further information: [www.hubergroup.de](http://www.hubergroup.de)

This Technical information reflects the current state of our knowledge. It is designed to inform and advise. We assume no liability for correctness. Modifications may be made in the interest of technical improvement.

All product, brand and company names used in these Technical Information sheets may be registered trademarks of their respective owners.