



COMBIDRY®

Fount concentrate for sheet-fed offset

8200 09

for water with a hydrogen
carbonate content
up to 250 mg/l

8200 19

for water with a hydrogen
carbonate content
above 250 mg/l

Application

COMBIDRY® has been developed specifically for use on offset printing presses with alcohol application units to accelerate the oxidative drying process of the inks. No more than 8 – 10% isopropanol is required.

Special properties

- Remarkable acceleration of ink drying.
- Printing plates run clean very fast.
- Formation of a stable, thin film of fount solution due to a specific reduction of surface tension.
- Good protection of printing plates.
- Prevents stripping of the ink rollers.
- Suitable for all types of printing plates.

Due to the specific formulation and to stabilise the active compounds in the product, the pH value of the fount solution is adjusted and stabilised at 6.0 ± 0.2 . There are two versions of COMBIDRY® available to allow you to set the pH value to within this range in conjunction with all tap water qualities. If you are not sure, we will gladly carry out an analysis of your water – at no charge – in order to determine which version you should be using.

Quantity to be added

The recommended addition is 4%.

Labelling

Hazardous Substances Ordinance (GefStoffV): irritant (Xi)
Safety data sheet available on request.

How supplied

10-kg plastic containers
25-kg plastic containers
220-kg plastic drums

Contact addresses for advice and further information: www.hubergroup.de

This Technical information reflects the current state of our knowledge. It is designed to inform and advise. We assume no liability for correctness. Modifications may be made in the interest of technical improvement.

All product, brand and company names used in these Technical Information sheets may be registered trademarks of their respective owners.