

Delivery cans/drums/containers for heatset inks

We would like to use this Technical Information sheet to give you, our customers, an overview of the different containers and their sizes in which you can purchase heatset inks.



2.5-kg vacuum-sealed can

190 x 126 mm
deep-drawn
two-piece
bright



10-kg drum

with wire handle
conical
tin plate
280 x 265 x 235 mm



25-kg drum

conical
tin plate
328 x 312 x 390 mm



216.5-l / 200-kg lid-type drum

made of sheet steel without beads
inside untreated
outside painted green
without inner PE sack
or
with inner PE sack
sheet thickness of 0.75 mm for shell
1 mm for base and lid
571.5 x 890 mm

**300-kg web offset container
3" TW horizontal outlet**

Filler opening	removable cover with 8 quick-release locks
Vent	1"
Outlet	horizontal at narrow end TW 3"
Basic dimensions	820 x 1020 mm
Height	1580 mm
Weight empty	127 kg
Max. capacity	300 kg



**500-kg web offset container
3" TW horizontal outlet**

Filler opening	removable cover with 8 quick-release locks
Vent	1"
Outlet	horizontal at narrow end, 3" TW male fitting
Valve	3" ball valve
Basic dimensions	840x 1040 mm
Height	1630 mm
Weight empty	196 – 200 kg
Max. capacity	500 kg



**MHM version
R3" perfection cock**

**HST version
3" ball valve**



**500-kg web offset container
4" vertical outlet**

Filler opening	removable cover with 8 quick-release locks
Vent	1"
Outlet	vertical, 4" TW male fitting
Valve	butterfly valve nom. diameter 100
Basic dimensions	840x 1040 mm
Height	1630 mm
Weight empty	196 – 200 kg
Max. capacity	500 kg



**1,000-kg web offset container
3" TW horizontal outlet**

Filler opening	removable cover with 8 quick-release locks
Vent	1"
Outlet	horizontal at narrow end, TW 3" male fitting
Valve	3" ball valve
Basic dimensions	1030 x 1230 mm
Height	1850 – 1940 mm
Weight empty	232 – 268 kg
Max. capacity	1,000 kg



1,000-kg web offset container 4" TW vertical outlet

Filler opening	removable cover with 8 quick-release locks
Vent	1"
Outlet	vertical, 4" TW male fitting
Valve	butterfly valve nom. diameter 100
Basic dimensions	1030 x 1230 mm
Height	1850 – 1940 mm
Weight empty	232 – 268 kg
Max. capacity	1,000 kg



1,000-kg web offset container 4" TW vertical and horizontal outlet

Filler opening	removable cover with 8 quick-release locks
Vent	1"
Outlet	vertical and horizontal 4" TW male fitting
Valve	butterfly valve nom. diameter 100
Basic dimensions	1030 x 1230 mm
Height	1850 – 1940 mm
Weight empty	232 – 268 kg
Max. capacity	1,000 kg



Contact addresses for advice and further information: www.hubergroup.de

This Technical information reflects the current state of our knowledge. It is designed to inform and advise. We assume no liability for correctness. Modifications may be made in the interest of technical improvement.